

Specifications

Model	ZPC-M847-S100
Processor	Adopt Intel Celeron dual core 1037u (22nm, 1.8GHz, 2MB second Cache)
Chipset	Adopt Intel NM70 express chipset
RAM	2G DDR3(can up to 8G)
Display port	Integrated Intel HD Graphic card 2500, Support 1*VGA, 1*LVDS display input
Expansion port	1*Mini-PCIE, Support wifi/3G, 1*M-SATA
Storage	1*MINI-SATA, 3*SATA
Audio	Integrated Realtek ALC662 6 sound channel
Network	1* Intel RTL8111E 1000M Lan, support wake on lan
I/O	6*COM (optional COM2,COM3 can support RS422 /485) 1* 12V DC_JACK input 1*LPT 1*VGA 1* RJ-45 LAN 6*USB2.0 1* Mic , 1*Audio
Built-in I/O	1* LVDS and LVDS INVERTER 1* GPIO 1*HDMI pin header 4*USB2.0 1* SIM
BIOS	AMI 32M BIOS, ACPI supported, support electricity boot
WDT	Support hardware reset (256 level, 0~255 sec)
Power supply	DC-12V
Temp	-20°C~80°C
Humidity	0~95% relative humidity, non-condensing
Dimension	196*204*70mm(L*W*H)

