



## Specifications

<b>Model</b>	ZPC-H6-X4
<b>Processor</b>	Support Intel® Celeron 1037 dual core (22nm,1.8GHZ, 2M second cache)
<b>Chipset</b>	Adopt Intel NM70 express chipset
<b>RAM</b>	1* SO DDRIII DDR3 1333/1066, MAX 8GB
<b>Display port</b>	Integrated Intel® HD Graphics 2500 Provide 1*VGA、1*HDMI、1*LVDS
<b>Expansion port</b>	1* Mini-PCIE slot, support WIFI/3G module 1* MSATA slot, support SSD/WIFI
<b>Storage</b>	2* SATAII
<b>Audio</b>	Integrated Realtek ALC662 6 sound channel Support MIC Line-out
<b>Network</b>	2* RTL8111E 1000M, support wake on lan
<b>I/O</b>	1* HDMI 1* VGA 2* RJ-45 6* USB 2.0 1* COM 1* Line Out, 1* Mic 1* 12V DC-JACK
<b>Built-in I/O</b>	2* PWROUT 2* USB2.0 1* LVDS (2*15Pin) 1* Mini-PCIE 1*Mini-SATA 2*SATA 1* ATX_12V(2*2pin)
<b>BIOS</b>	32MB SMT Flash ROM
<b>WDT</b>	Support hardware reset (256 level, 0~255 sec)
<b>Power supply</b>	DC_12V
<b>Temp</b>	-10℃~60℃
<b>Humidity</b>	0~95% relative humidity, non-condensing
<b>Dimension</b>	211*174*45(L*W*H)

